

SWEeper-HG

SPEED GATES

Sweeper-HG is a modification of the Sweeper speed gate, featuring tall glass blades that increase the overall height of the speed gate to 1800mm. The passage width can range from 550 to 900mm, offering flexibility to suit different requirements. This model of the speed gate is specifically designed for applications that demand a heightened level of security. The high swing glass blades effectively prevent the transfer of objects above the turnstile and deter any attempts to overjump it. The taller glass blades provide an added layer of protection, making it an ideal choice for environments that prioritize both security and aesthetics.



PERFECT SOLUTION WITH HIGHER DEGREE OF SECURITY

550
mm
PASSAGE WIDTH

30
pers/min
SINGLE ACCESS FLOW RATE

60
pers/min
FREE ACCESS FLOW RATE

0,7
0,9
sec
OPENING / CLOSING

41
PROTECTIVE LEVEL

ANTI-TAILGATING

BI-DIRECTIONAL

ACCESS CONTROL SYSTEM

MANUAL CONTROL

Key features:

- BMDrive® - a reliable mechanism with a powerful BLDC gear motor ensures long-term, maintenance-free operation.
- The speed gate is equipped with a smart self-diagnostic system.
- An innovative controller with an OLED display and buttons allows for easy setup and configuration without the need for special programmers.
- Digital control of force and leaf speed, combined with safety sensors, prevents accidents and ensures the safety of individuals, even in cases of unauthorized passage.
- The sensor system enables the detection of individuals with luggage or allows for a free exit without the need for identification.
- Elegant cabinets come equipped with integrated LED lighting that displays the access status and card reader area.
- The housing design and top lid can be customized to meet specific preferences.
- Can be seamlessly integrated with any type of access control system.
- A wired remote control panel is included as part of the standard kit.
- Low power consumption.
- In the event of a power failure, the leaves can be manually opened (fail-safe).



www.tiso.global
 +380 (44) 291-21-11
 sales@tiso.global




CE UK
CA

TECHNICAL SPECIFICATIONS /

Model	Sweeper-HG 550	Sweeper-HG 900
Cabinet width, mm	192	
Cabinet length, mm	1434	
Cabinet height, mm	1010	
Leaves height, mm	1500/1800	
Passage width, mm	550	900
Opening/closing time, sec	0,7	0,9
Mechanism	BMDrive® servodrive (BLDC)	
Blocking system	ToothLock®	
Emergency mode (fire-alarm)	Free entry/exit (leaves are opened automatically)	
Power fail	Fail safe (gates could be opened manually — standard)	
MCBF, cycles	10 000 000	
MTTR, min	< 25	

Electrical Specifications:

Maximum power consumption, W	160
Voltage	From the AC (100-240)V, 50/60Hz; from a DC source 12 V
Indication	DotLights®, RFIDLights®, EdgeLights®
Finishing	
Standard housing	Brushed SS AISI 304
Available housing	Brushed SS AISI 316; Polished SS AISI 304; Polished SS AISI 316; Powder coated RAL



Specifications are subject to change without prior notice



www.tiso.global



+380 (44) 291-21-11



sales@tiso.global



STANDARD FEATURES /



LED INDICATIONS

Introducing our RFIDLight® and DotLight® features, designed to captivate attention and enhance user experience:
 RFIDLight®: Illuminates card reader area.
 DotLight®: Displays access status.



CONTROL PANEL

Included in the standard set, our wired control panel offers versatile functionality:
 Facilitates single passage and free passage modes.
 Enables access blocking and activation of the anti-panic function.



SAFETY SENSORS, ANTI-TAILGATING FUNCTION

Our high-precision sensors excel in identifying unauthorized passage, effectively preventing tailgating by detecting two or more individuals. Additionally, our safety sensors ensure secure passage for individuals with luggage or trolleys, ensuring gates remain open until the passage is completed.



EDGELIGHTS®

Impressive illumination of the glass housing can be in three colors (standard), marking the status of passage: blue - standby mode; green - access authorized; red - access denied.



UPS FUNCTION

Introducing our advanced UPS system, seamlessly integrated to automatically switch power to the backup battery during outages. This ensures uninterrupted functionality of our speed gate, empowering you to utilize all features even in the event of a power failure.



PLACE FOR RFID INSTALLATION

RFID installation space included in standard speedgate configuration.

ADDITIONAL OPTIONS /



PATTERN APPLICATION

Customize your speed gates with unique signatures, patterns, logos, and more, seamlessly placed on the leaves, housing, or top lid for a distinctive touch.



INTEGRATION OF CUSTOMISED ACS

Seamless integration of various access control systems upon request, including RFID devices, coin acceptor push buttons, fingerprint scanners, face recognition, barcode readers, and QR code readers.



CARD COLLECTOR INTEGRATION

Integration of automatic card collector directly into the speed gate housing is possible.



MP3 AUDIO MODULE

Enjoy a comprehensive audio signaling system for various gate events: access / authorised access/ closing / opening / alarm.



TWIC WIRELESS CONTROL PANEL

TiSO TWIC offers remote control for multiple lines of turnstiles. With its space-saving 10" touchscreen display, it can be conveniently placed at reception desks or within security control areas.



PASS COUNTER

Automatically counts the number of passes for efficient tracking and management.




FOOTPRINT ILLUMINATION

Illuminate the footprint of the speed gate housing with LED lighting. Customize the color of the light to suit your preferences.



SUPER CAPASITOR


Ensure uninterrupted operation with our free power package, enabling emergency automatic one-time opening of the speed gate.



EXIT BUTTON

Introducing a convenient touch-free button option for organizing exits effortlessly.

ADDITIONAL OPTIONS /



RANDOMISER

This mechanism autonomously selects individuals for verification without human intervention, ensuring impartiality.



MOBILE PLATFORM

Enables rapid temporary installation of the speed gate, ideal for areas where floor drilling is not possible.



RFID READERS T-PROX MINI

The reader is compatible with 125 kHz cards, Mifare, Mifare Plus, as well as mobile credentials U-Prox ID via NFC and 2.4 GHz radio.



ALARM BUZZER

Audible alarm activated upon unauthorized access.